

(12) United States Patent

Barker

(10) Patent No.:

US 6,559,370 B1

(45) Date of Patent:

May 6, 2003

(54)	SUBMARINE COUNTERMEASURE			
` '	VEHICLE WITH FOLDING PROPELLER			

(75) Inventor: William P. Barker, Bristol, RI (US)

(73) Assignce: The United States of America as

represented by the Secretary of the

Navy, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl.	No.:	10/214,527
------------	------	------------

(22) Fi	led:	Aug.	6	200

(51)	Int. Cl.7	F421	B 17/00
(52)	U.S. Cl.	114/20.2: 114/20.1: 1	14/236

114/238; 244/3.24; 244/3.27; 244/3.28; 244/3.29; 244/63; 416/138; 416/142

Field of Search 244/3.24, 3.27, (58)244/3.28, 3.29, 63; 114/20.1, 20.2, 236,

238; 416/138, 142

References Cited (56)

U.S. PATENT DOCUMENTS

938,290 A	• 10/1909	Thompson 416/138
2,481,751 A	• 9/1949	Godfrey 416/142
2,608,257 A	* 8/1952	James 416/142
2,847,960 A	* 8/1958	Endrezze 114/20.1
3,690,595 A	• 9/1972	Rusbach 244/3.27
3,790,104 A	* 2/1974	Jones 244/3.27
3,918,664 A	• 11/1975	Grosswendt 244/3.28
4,440,360 A	• 4/1984	Hallstrom 244/3.28

				Baubry 244/3.28
				Blaha 114/338 Alford et al 244/3.23
				Kuhnle et al 244/3.2
6.367.401	B1	٠	4/2002	Correia et al

FOREIGN PATENT DOCUMENTS

CH	3320850	٠	11/1958
CH	375628	•	11/1961
DE	1195204	. •	6/1965
GB	1188651	•	4/1970

^{*} cited by examiner

Primary Examiner-Michael J. Carone Assistant Examiner-John Richardson (74) Attorney, Agent, or Firm-James M. Kasischke;

Michael J. McGowan; Michael F. Oglo

ABSTRACT

A submarine countermeasure vehicle includes an elongated body for supporting a countermeasure device, and a propulsion assembly mounted on an after end of the body. The propulsion assembly includes a rotatable propeller hub, propeller blades mounted on the hub and moveable between a first position wherein the blades extend substantially radially outwardly from the hub, and a second position wherein the blades extend generally axially of the hub. A spring is mounted on each of the blades and in the hub, the spring biasing the blades toward the first position, but of sufficient flexibility to permit the blades to move to the second position upon launch of the vehicle from an underwater launch tube.

5 Claims, 5 Drawing Sheets

